



Product Specifications

FS1251



Fuel/Water Separator, Spin-On

Fleetguard® FS1251 premium fuel water separator spin-on works to remove water and other particulates and ensures clean fuel is delivered to your engine.

[View product on Fleetguard.com](http://Fleetguard.com)

Specifications

Thread Size	M16 X 1.5-6H INT	Length	5.63 inch / 142.90 mm
Largest OD	3.02 inch / 76.71 mm	Gasket Inside Diameter	2.46 inch / 62.48 mm
Gasket OD	2.72 inch / 69.09 mm	Standpipe	YES
EMULSIFIED WATER SEPARATION	90%	Test Specification	ISO TR13353
Primary Particle Efficiency	17.30 micron (c) @ 96%	Rated Flow	19.81 gpm / 75.00 L/min

Related Parts

Replaces	FF5047	FS1226
Filter Used With	3311505S	
Upgrade Of	FF5052	

Is A Longer Version Of FS1235
Uses Service Gasket 3311919

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved