



Product Specifications

FS19591



Fuel/Water Separator, Spin-On

Fleetguard® FS19591 fuel water separator spin-on works to remove water and other particulates and ensures clean fuel is delivered to your engine. Bottom of shell has internal threads to attach bowl. Bowl has external threads.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

Thread Size	1-14 UNF-2B	Length	8.50 inch / 215.90 mm
Largest OD	4.25 inch / 107.95 mm	EMULSIFIED WATER SEPARATION	96% / 96.00 %
Efficiency Test Std	SAE J905	Rated Flow	7.57 L/min
Gasket OD	3.58 inch / 91.00 mm	Test Specification	ISO 19438

Product Comments

Bottom of shell has internal threads to attach bowl. Bowl has external threads. For drain only version with no sensor port use FS19934

Related Parts

Uses Service Part 3957279S

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved