



Product Specifications

FS19596



Fuel/Water Separator, Spin-On

Fleetguard® FS19596 premium fuel water separator spin-on works to remove water and other particulates and ensures clean fuel is delivered to your engine.

[View product on Fleetguard.com](http://Fleetguard.com)

Specifications

Thread Size	1-14 UNS-2B	Media Type	StrataPore
Largest OD	3.69 inch / 93.83 mm	Length	9.78 inch / 248.31 mm
Gasket Inside Diameter	2.46 inch / 62.53 mm	Gasket OD	2.83 inch / 71.98 mm
Standpipe	YES	EMULSIFIED WATER SEPARATION	95%
Test Specification	CECO ES14225	Primary Particle Efficiency	7.90 micron (c) @ 98.7%

Related Parts

Uses Element	FH22239
Upgrade Of	FS1003

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved