



Product Specifications

FS19652



Fuel/Water Separator, Spin-On, StrataPore

Fleetguard® FS19652 fuel water separator spin-on works to remove water and other particulates and ensures clean fuel is delivered to your engine.

[View product on Fleetguard.com](http://Fleetguard.com)

Specifications

Media Type	Stratapore	Largest OD	3.69 inch / 93.60 mm
Gasket Inside Diameter	2.46 inch / 62.50 mm	Gasket OD	2.83 inch / 72.00 mm
Test Specification	SAE J905	Thread Size	13/16-18 UNF 2B
Primary Particle Efficiency	5.00 micron @ 95%	Rated Flow	1.00 gpm / 3.80 L/min

Product Comments

The drain valve and the pipe from the previous filter need to be reused. Please refer to the FS19652V for the filter with drain valve and pipe.

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Atmus Filtration customers "as is" without any warranties, express or implied,

including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved