



# Product Specifications

FS19728

## Fuel/Water Separator, Cartridge, EleMax



Fleetguard® FS19728 standard size EleMax™ fuel filter protects vital fuel system components. Its patented control valve provides full use of the filter, fits Fuel Pro® and many Diesel Pro® models, has multiple micron ratings for OEM compliance, and is biodiesel compatible.

[View product on Fleetguard.com](http://Fleetguard.com)

## Specifications

Media Type	StrataPore	End 1 ID	0.66 inch / 16.76 mm
End 2 OD	3.82 inch / 97.03 mm	Largest OD	3.82 inch / 97.03 mm
Length	6.79 in / 178.81 mm	EFFICIENCY, TWA BY SAE J 1985	98.7%
EMULSIFIED WATER SEPARATION	95%	FREE WATER SEPARATION	95%
MICRON RATING BY SAE J 1985	25.00 micron	Largest End ID	1.28 in / 32.51 mm

## Related Parts

Filter Used With	FH23605M	FH23603	FH23625M	FH23604M
Uses	FH23606M	FH23308	FH23624M	

<b>Element</b>	FH23627	FH23617M
<b>Replaces</b>	FS19728G	

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved