



# Product Specifications

## FS19730



### Fuel/Water Separator, Cartridge, StrataPore

Fleetguard® FS19730 fuel filter offers optimum protection from contaminants like dirt and water, an engine's biggest enemies, to protect vital fuel system components.

[View product on Fleetguard.com](#)

## Specifications

Media Type	StrataPore	Length	4.44 in / 112.90 mm
End 1 ID	0.66 inch / 16.76 mm	Largest OD	3.50 inch / 88.82 mm
End 2 OD	3.48 inch / 88.39 mm	EFFICIENCY, TWA BY SAE J 1985	98.7%
EMULSIFIED WATER SEPARATION	95%	FREE WATER SEPARATION	95%
MICRON RATING BY SAE J 1985	7.00 micron	Rated Flow	3.78 L/m
Primary Particle Efficiency	0.99	Largest End ID	1.28 in / 32.51 mm
Length / Overall Height	4.44 inch / 112.90 mm		

## Related Parts

<b>Filter Used</b>	FH23501	FH23200	FH23502	FH23201
<b>With</b>	FH23500	FH23202		
<b>Uses</b>	FH23517			
<b>Element</b>				
<b>Replaces</b>	FS19730G			

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved