



Product Specifications

FS19732

Fuel/Water Separator, Spin-On



Fleetguard® FS19732 fuel water separator spin-on works to remove water and other particulates and ensures clean fuel is delivered to your engine.

[View product on Fleetguard.com](http://Fleetguard.com)

Specifications

Media Type	StrataPore	Thread Size	1-14 UNS-2B
Length	7.96 in / 202.29 mm	Largest OD	3.69 inch / 93.83 mm
EFFICIENCY, TWA BY SAE J 1985	0.99	EMULSIFIED WATER SEPARATION	95%
FREE WATER SEPARATION	0.95	Standpipe	NO
Gasket Inside Diameter	2.46 inch / 62.48 mm	Gasket OD	2.83 inch / 71.88 mm
MICRON RATING BY SAE J 1985	25.00 micron	Seam OD	3.67 in / 93.17 mm

Product Comments

Cummins QSB, QSC, QSL engines Stratapore Media

Related Parts

Includes	FH21080 FH22264	FH21101	FH21108	FH21049
Uses Service Part	3942834S			
Filter Used With	FH126	3944287S		
Uses Element	FH22239			

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved