



Product Specifications

FS19766



Fuel/Water Separator, Cartridge, E

Fleetguard® FS19766 plus size EleMax™ fuel filter protects fuel system components. Its patented control valve provides use of the filter, fits Fuel Pro® and many Diesel Pro® models. Multiple micron ratings for OEM compliance, and is biodegradable.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

Length / Overall Height	7.03 inch / 178.61 mm	Media Type	StrataPore
End 1 ID	0.66 inch / 16.76 mm	Length	6.79 in / 172.47 mm
End 2 OD	4.21 inch / 106.93 mm	Largest OD	4.21 inch / 106.94 mm
EFFICIENCY, TWA BY SAE J 1985	98.7%	EMULSIFIED WATER SEPARATION	95% / 95.00 %
FREE WATER SEPARATION	95%	MICRON RATING BY SAE J 1985	5.00 micron
Rated Flow	11.35 L/m	Primary Particle Efficiency	98.7%
Largest End ID	1.28 in / 32.51 mm	Gasket Inside Diameter	0.66 inch / 16.76 mm

Product Comments

Plus size version of FS19761 for Extended Service Intervals when used in FH230 Series Fuel Pro's or standard for FH234 Series Industrial Pro

Related Parts

Filter Used With FH23441

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved