



Product Specifications

FS19934



Fuel/Water Separator, Spin-On

Fleetguard® FS19934 fuel water separator spin-on works to remove water and other particulates and ensures clean fuel is delivered to your engine. Drain only version with no sensor port.

[View product on Fleetguard.com](http://Fleetguard.com)

Specifications

Thread Size	1-14 UNF-2B	Length	11.48 inch / 291.57 mm
Largest OD	4.24 inch / 107.67 mm	Gasket Inside Diameter	3.56 inch / 90.55 mm
Gasket OD	3.94 inch / 99.95 mm	Standpipe	NO
EMULSIFIED WATER SEPARATION	95%	Hydrostatic Burst Minimum	299.93 psi / 2068.50 kPa
Test Specification	SAE J905	Rated Flow	2.00 gpm / 7.57 L/min

Product Comments

Drain only version with no sensor port Drain only option for FS19591

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided asa

convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved