



Product Specifications

FS20007



Fuel/Water Separator, Spin-On

Fleetguard® FS20007 premium fuel water separator spin-on works to remove water and other particulates and ensures clean fuel is delivered to your engine.

[View product on Fleetguard.com](http://Fleetguard.com)

Specifications

| | | | |
|------------------------------|-----------------------------|--------------------------------|--------------------------|
| Largest OD | 4.25 inch / 107.95 mm | Length | 9.33 inch / 237.10 mm |
| Gasket OD | 4.14 inch / 105.28 mm | EMULSIFIED WATER SEPARATION | 0 |
| Media Type | Cellulose | Test Specification | ISO 19438 |
| Hydrostatic Burst Minimum | 199.81 psi / 1378.00 kPa | Thread Size | 1-14 UNF 2B |
| Rated Flow | 2.01 gpm / 7.60 L/min | | |

Related Parts

Replaces FS19820 FS19995

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided asa

convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved