



Product Specifications

FS20009



Fuel/Water Separator, Spin-On

Fleetguard® FS20009 fuel water separator spin-on works to remove water and other particulates and ensures clean fuel is delivered to your engine.

[View product on Fleetguard.com](#)

Specifications

Length	8.01 inch / 203.56 mm	Largest OD	3.43 inch / 87.12 mm
EMULSIFIED WATER SEPARATION	0	Hydrostatic Burst Minimum	299.93 psi / 2068.50 kPa
Primary Particle Efficiency	25.00 micron (c) @ 98.7%		

Product Comments

Do not use the original canister. FS20009 replaces both the element and the canister.
Removal of the Baldwin thread adaptor is required to use FS20009 which is intended to be used with the OEM filter head.

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided asa convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property.Atmus Filtration does not warrant the accuracy nor completeness of the

Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved