



Product Specifications

HF30014

Hydraulic Filter, Spin-On



Fleetguard® HF30014 hydraulic spin-on filter with synthetic media is designed to help keep your precision hydraulic systems running as intended, providing a solution for various applications. This filter meets or exceeds the equipment OEM quality and performance and is the first aftermarket replacement available on the market today, bringing your operation top-quality performance and an overall unbeatable total cost of ownership.

[View product on Fleetguard.com](http://Fleetguard.com)

Specifications

Thread Size	1.00 1/2-16 UN-2B	Largest OD	3.68 inch / 93.47 mm
Length	5.82 inch / 147.83 mm	Seam OD	3.72 in / 94.49 mm
Gasket Inside Diameter	2.97 inch / 75.34 mm	Gasket OD	3.44 inch / 87.50 mm
Standpipe	NO	TWA MICRON @ BETA=2	3.00 micron
TWA MICRON @ BETA=20	7.50 micron	TWA MICRON @ BETA=200	12.00 micron
TWA MICRON @ BETA=75	9.50 micron	Length / Overall Height	5.82 inch / 147.83 mm
Particle Size at Beta 200	12.00 micron (c)		

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved