



Product Specifications

HF35209

Hydraulic Filter, Cartridge



Photo Not Available



Fleetguard® HF35209 hydraulic cartridge filter is designed to help keep your precision hydraulic systems running as intended, providing a solution for various applications. This filter meets or exceeds the equipment OEM quality and performance and is the first aftermarket replacement available on the market today, bringing your operation top-quality performance and an overall unbeatable total cost of ownership.

[View product on Fleetguard.com](#)

Specifications

Largest OD	3.90 inch / 99.00 mm	Largest End ID	1.59 inch / 40.50 mm
Length	8.43 inch / 214.00 mm	Gasket Inside Diameter	1.56 inch / 39.60 mm
Particle Size at Beta 75	35.00 micron (c)	Efficiency Test Std	ISO 16889
Pressure Valve Opening Pressure	175.00 kPa	Gasket OD	1.84 inch / 46.66 mm
Pressure Valve	Yes	Test Specification	ISO 16889
Length / Overall Height	8.43 inch / 214.00 mm		

Product Comments

Delivered without spring

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved